

Companion Plus



PRICE PRO SERIES



Low Cost Receipt and Label Printer for Store and Office

All at the industry's lowest price!

Print customer receipts at your sales counter or labels for shipping, mailing and inventory with the Companion Plus. Versatile, compact, and durable, the Companion Plus is the perfect mate for cash registers, computers, and telecommunication devices.

With its small footprint and high quality direct thermal printing, the Companion Plus also offers liner-free label printing. Print product, shipping, specimen, file folder, video and diskette labels. And when desk space is in really short supply, the Companion Plus can be wall mounted.

Designed for use in many applications, including:

- Receipt printing in restaurants and retail stores
- Transaction receipts in financial institutions
- Mailing, parcel shipping and specimen labeling

All for a price far below other direct thermal printers!

Another PricePro Printer from Eltron.

All Eltron Printers are built to tough ISO 9002 standards.

Companion Plus Specifications

General Specifications

- 64 Kb SRAM standard
- Reflective sensor for black marks and notched labels
- Internal label and receipt roll holder
- Easy to load paper path
- Easy to use ELP2 command language
- Batch or on-demand printing
- Prints text, graphics and bar codes in four directions: 0°, 90°, 180° and 270°
- Graphics, line and box drawing features, PCX bit map supported
- Line and page print modes
- Supports most popular ESCPOS™ commands

Printing

- Direct thermal printing
- Printing speed of 1" (25.4mm) per second
- 203 dpi (8 dots/mm) print resolution
- Maximum print width: 2.83" (72mm)
- Maximum print length: 4" (101.6mm)

Bar Codes

- Code 39
- Code 128 subsets A, B and C
- Interleaved 2 of 5
- UPC-A, UPC-E, 2 & 5 digit add-on
- EAN-8, EAN-13, 2 & 5 digit add-on
- POSTNET
- MaxiCode
- PDF-417
- Bar codes with or without human readable text
- Bar codes can be printed in four directions: 0°, 90°, 180° and 270°

Fonts & Graphics

- International character sets standard
- Horizontal and vertical magnification of fonts up to 4x
- Fonts can be printed in four directions: 0°, 90°, 180° and 270°
- Character sets: 5.6 cpi (16 column), 12.7 cpi (36 column), 14.5 cpi (41 column), 16.9 cpi (48 column) and 20.3 cpi (58 column)
- Supports line and box drawings

Media Handling

- Reflective sensor for back marks and notched labels

Media

- Materials: Thermal direct sensitive labels and papers
- Type: Roll-fed, die cut (notched thermal labels) and continuous roll thermal receipt paper
- Maximum media width receipt paper: 3" (76mm)
- Minimum media width receipt paper: 2.6" (66mm)
- Maximum media width labels: 3.1" (79mm)
- Minimum media width labels: 3.1" (79mm), .5" (12.7mm) O.D. core for labels and receipt
- Maximum media length at thickness:

Length	Thickness
1750" (44.6m)	2.2 mil (.056mm)
1170" (29.7m)	3.2 mil (.081mm)
875" (22.3m)	4.2 mil (.107mm)

Communications Interface

- RS232C (RJ11 Connector)
- TTL handshaking
- Daisy chain port
- Cash drawer kicker

Mechanical

- Width 4" (102mm)
- Depth 5" (125mm)
- Height 6" (153mm)
- Weight 4.2 lbs (1.9kg) including power supply

Electrical

- Nominal Voltage: (Linear) 120V/220V, 60/50 Hz
- Complies with FCC Class B and CE requirements; Built to CUL and TUV requirements

Environmental

- Operating Temperature: 40°F to 105°F (5°C to 40°C)
- Storage Temperature: -40°F to 140°F (-40°C to 60°C)
- Humidity: 10% to 90% non-condensing
- Ventilation: Free air

Options

- Liner free label model
- Windows™ printer driver
- Create-A-Label 3 for Windows™
- ESCPOS™ model
- Companion starter kit for all applications

Eltron

THE ECONOMIES ARE ENGINEERED IN



©1998 Eltron International. All Rights Reserved. Specifications subject to change without notice. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. 820007-014 revE

Corporate Headquarters

Eltron International, Inc.
1001 Flynn Road
Camarillo, CA 93012-8706
United States of America
Telephone +1 805 579 1800
Fax +1 805 579 1808
Toll free in US 800 344 4003
e-mail sales@eltron.com
Web www.eltron.com

European Headquarters

Eltron International, Inc.
Eltron House
Unit 2, The Business Centre
Molly Millars Lane
Wokingham, Berkshire RG41 2QZ
United Kingdom
Telephone +44 118 977 0300
Fax +44 118 989 5762
e-mail eurosales@eltron.com

Branch Office

Eltron International, Inc.
50, rue Marcel Dassault
92100 Boulogne-Billancourt
France
Telephone +33 1 55 20 93 93
Fax +33 1 55 20 93 99
e-mail frsales@eltron.com

Asia Pacific Headquarters

Eltron International, Inc.
60 Martin Road
#07-18 Trademart Singapore
239065 Singapore
Telephone +65 7333 123
Fax +65 7338 206
e-mail asiassales@eltron.com