

DIRECT THERMAL/
THERMAL TRANSFER
PRINTER

EasyCoder™ 4420

Benefits:

- **Unsurpassed Reliability**
Based on the proven design of other successful Intermec printers, the 4420 performs non-stop, delivering fast, reliable printing at an economical price.
- **Versatile**
High quality printing and a 11.2 cm (4.4") print width makes the 4420 ideal for a variety of applications.
- **Continuous Duty Cycle**
The 4420 is built for demanding, high volume, harsh printing environments where round-the-clock performance is required.
- **Unequaled Print Registration**
Intermec's exclusive PrecisionPrint™ technology offers incomparable image registration on a wide range of labeling applications.
- **IPL Compatible**
The 4420 with IPL3™, Intermec's latest printer language, is backward compatible with earlier Intermec IPL™ printers.



Superior performance at an economical price distinguish the 4420 as a rugged, reliable, high-volume, continuous duty cycle printer not normally associated with high-end performance printers. Unlike many printers in this price range, the 4420, housed in an all-steel casing, is ideal for harsh or adverse environments. With 32-bit RISC processing and 20.32cm (8")/second print speed, the 4420 is both fast in image formatting and time-to-first print.

Featuring a variety of options, this 203 dpi printer is easily configurable to suit your particular environment. The 4420 comes standard with bidirectional parallel and high speed RS-232 communications interfaces. Options such as full batch take

up with auto-peel, cutter, internal IBM Coax™ and Twinax™ adapters and external ethernet adapter are all available.

Originally introduced on the EasyCoder 3240, PrecisionPrint™ technology keeps the printed image within the tightest tolerance, whether printing in batch or on demand operation. Even on tough labels where problems with label registration show up immediately, as with oddly shaped or small labels or those labels with a preprint, the 4420 excels with this proven technology.

With robust performance, fast throughput and all-steel housing, the 4420 is built to take it in harsh, industrial, manufacturing, distribution and warehousing environments.

EasyCoder™ 4420

General

Direct Thermal and Thermal Transfer Printer for self-adhesive label, ticket and tag applications. Auto-peel, batch take-up and cutter optional

Model

EasyCoder 4420

Physical Characteristics

Depth: 43.82 cm (17.25")

Height: 41.91 cm (16.5")

Width: 24.8 cm (9.75")

Weigh: 19.35 kg (43 lbs.)

Print Specifications

Thermal Transfer and Direct Thermal Printing

Selectable Print Speeds:

5.08cm (2"), 7.62 cm (3"), 10.16 cm (4"), 12.70 cm (5"), 15.24 cm (6"), 17.78 cm (7"), or 20.32 cm (8") centimeters/inches per seconds

203 dots per inch (8 dots/mm) print resolution

Maximum Width: 11.2 cm (4.4")

Maximum Length: Unlimited

Media Specifications

Style: Roll-feed, die-cut, continuous of fanfold labels, tags, or tickets

Type: Plain paper thermal transfer or thermal sensitive papers

Maximum Media Width: 11.4 cm (4.5")

Minimum Media Width: 1.9 cm (.75")

Maximum Media Length: 121.9 cm (48")

Minimum Media Length: 1.3 cm (.5")

Thickness: .08 mm to .3 mm (.0003 to .012")

Supply Roll Capacity: 152.4 m (6000" linear)

Ribbon Specifications –

Type: Wax, wax/resin, resin

Standard Widths: 5.38 cm (2.12"),

7.62 cm (3.0"), 10.41 cm (4.1"),

11.43 cm (4.5")

Length: 457 m (18,000")

Interface

IEEE 1284 Parallel, RS-232 with software selectable rates of 1,200 to 115K baud, RS-422

Font Specifications

21 resident bit-mapped fonts (includes OCR-A and OCR-B), 3 resident outline fonts, supports user-defined fonts and graphics, supports True Type fonts

Software

IPL3™, Compressed Graphics, GLOBE™, Backward Compatibility with 86XX and IPL2™

Character Sets

Unicode, all single byte codepage, all doublebyte codepage

Power Supply

110, 115, 200, 230 VAC;
50Hz to 60Hz

Environment

Operating Temperature:
+5° to 40°C (40° to 104°F)

Storage Temperature:
0° to 49°C (32° to 120°F)

Humidity: 10 to 90% (non condensing)

Ventilation: Free air

Bar Code Symbologies

UPC/EAN, I 2 of 5, Code 2 of 5, Codabar, Code 11, Code 16K, Code 39, Code 49, Code 93, Code 128, HIBC, POSTNET, Code One, PDF 417, Maxicode, Data Matrix, and QR Code

Regulatory Approvals

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

Options

Full batch take up with auto-peel, internal coax, internal, twinax, 8MB expansion image DRAM, 4MB Flash storage expansion, 16MB Flash storage expansion, cutter, Ethernet adaptor

**Where
Information
Gets Down
To Business™**

North America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Norand Mobile Systems Division • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Amlech Systems Division • 19111 Dallas Parkway, Suite 300 • Dallas, Texas 75287-3106 • 1 (800) 923-4824 toll-free • 1 (972) 733-6600 tel • 1 (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastern Road • Reading, Berkshire, RG1 8BT • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax
Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax

Label Products and Supplies • North America • 1 (513) 874-5882 tel • 1 (513) 874-8487 fax • or 1 (800) 227-9947 tel • 1 (800) 227-1707 fax • Latin America/Asia Pacific • 1 (513) 870-7930 Int'l phone • 1 (513) 874-3613 Int'l fax • Europe/Middle East/Africa +31 24 372 3100 tel • +31 24 378 0070 fax

World-Wide Fax Document Retrieval Service • 1 (650) 637-2603 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

Copyright © 1998 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. 608371 9/98