

DIRECT THERMAL/
THERMAL TRANSFER
PRINTER

EasyCoder™ 4440

Benefits:

- **Industry-Proven Design**
Building on the success of our highly successful Intermec printers, the 3240, 3440 and 4420, the 4440 combines proven engineering for optimal reliability, throughput and print quality
- **Exceptional Print Quality**
The 4440 incorporates 400 dpi print technology for superior graphics, complex 2D symbologies and small fonts with exceptional print quality found only on Intermec printers
- **Unequaled Print Registration**
Intermec's patent-pending PrecisionPrint™ technology offers extremely accurate image registration even under adverse printing conditions
- **IPL Compatible**
The 4440 with IPL3™, Intermec's latest printer language, makes it backward compatible with other printers in the Intermec family as well as offers international language support and enhanced Windows® compatibility



Setting a new price/performance standard within the industry, the 4440 not only is rugged and reliable but also offers high quality 400 dpi print resolution at a fast 20.32 (8")/second print speed. Unlike many printers in this category, the 4440, housed in an all-steel casing, is ideal for harsh environments.

Powerful Intermec printers with 400-dpi technology not only drastically improves image quality but has other advantages too. With 400-dpi, the capability to print bar codes at a wide range of X dimensions and ratios is greatly enhanced. While users of 300-dpi technology can print some industry standard symbologies within tolerance, users of 400-dpi technology can print the same symbologies and precisely meet exacting industry standards. Also, the greater dot resolution results in the capability

to fit more information on a smaller label, thus resulting in money saved on labels and ribbons.

Based on the design of the 3240, PrecisionPrint™ technology keeps the printed image within the tightest tolerances whether printing in batch or on demand operation. Even on tough labels where problems with image registration show up immediately, as with oddly shaped or small labels or those labels with a preprint, the 4440 excels with this proven technology.

Simply put, 400-dpi technology coupled with a 11.2 cm (4.4") print width meets your industry's compliance specification not only today but also tomorrow.

EasyCoder™ 4440

General

Direct Thermal and Thermal Transfer Printer for self adhesive label, ticket and tag applications. Auto-peel batch take-up and cutter optional.

Model

EasyCoder 4440

Physical Characteristics

Depth: 43.82 cm (17.25")

Height: 41.91 cm (16.5")

Width: 24.77 cm (9.75")

Weight: 19.35 kg (43 lbs.)

Print Specifications

Thermal Transfer and Direct Thermal Printing

Selectable Print Speeds:

5.08 cm (2"), 7.62 cm (3"),

10.16 cm (4"), 12.70 cm (5"),

15.24 cm (6"), 17.78 cm (7"),

or 20.32 cm (8")

centimeters/inches per seconds

16 dots per mm (406 dots per inch) print resolution

Maximum Width: 11.18 cm (4.4")

Maximum Length: Unlimited

Media Specifications

Style: Roll-feed, die-cut, continuous of fanfold labels, tags, or tickets

Type: Plain paper thermal transfer or thermal sensitive papers

Maximum Media Width: 11.43 cm (4.5")

Minimum Media Width: 1.91 cm (.75")

Maximum Media Length: 121.92 cm (48")

Minimum Media Length: 1.27 cm (.4")

Thickness: .08 mm to .3 mm (.0003 to .012")

Supply Roll Capacity: 52.4 m (6000" linear)

Ribbon Specifications

Type: Wax, wax/resin, resin

Standard Widths: 5.38 cm (2.12"),

7.62 cm (3.0"), 10.41 cm (4.1"),

11.43 cm (4.5")

Length: 457.2 m (18,000")

Interface

IEEE 1284 Parallel, RS-232 with software selectable rates of 1,200 to 115K baud, RS-422

Font Specifications

21 resident bit-mapped fonts (includes OCR-A and OCR-B), 3 resident outline fonts, supports user-defined fonts and graphics, supports True Type fonts

Software

IPL3™, Compressed Graphics, GLOBE™, Backward Compatibility with 86XX and IPL2™

Character Sets

Unicode, all single byte codepage, all doublebyte codepage

Power Supply

110, 115, 200, 230V AC, 50Hz to 60Hz

Environment

Operating Temperature: 4°-40°C (40° to 104°F)

Storage Temperature: 0°-49°C (32° to 120°F)

Humidity: 10 to 90% (non condensing)

Ventilation: Free air

Bar Code Symbolologies

UPC/EAN, I 2 of 5, Code 2 of 5, Codabar, Code 11, Code 16K, Code 39, Code 49, Code 93, Code 128, HIBC, POSTNET, Code One, PDF 417, Maxicode, Data Matrix, and QR Code

Regulatory Approvals

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

Options

Full batch take up with auto-peel internal coax, internal, twinax, 8MB expansion image DRAM, 4MB Flash storage expansion, 16MB Flash storage expansion, cutter, Ethernet adaptor.

**Where
Information
Gets Down
To Business™**

North America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Norand Mobile Systems Division • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Amlech Systems Division • 19111 Dallas Parkway, Suite 300 • Dallas, Texas 75287-3106 • 1 (800) 923-4824 toll-free • 1 (972) 733-6600 tel • 1 (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastem Road • Reading, Berkshire, RG1 8BT • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax

Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax

Label Products and Supplies • North America • 1 (513) 874-5882 tel • 1 (513) 874-8487 fax • or 1 (800) 227-9947 tel • 1 (800) 227-1707 fax • Latin America/Asia Pacific • 1 (513) 870-7930 Int'l phone • 1 (513) 874-3613 Int'l fax • Europe/Middle East/Africa +31 24 372 3100 tel • +31 24 378 0070 fax

World-Wide Fax Document Retrieval Service • 1 (650) 637-2603 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

Copyright © 1998 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. 60856 8/98